

■硬質塩化ビニール管 寸法許容差及び重量

JIS K 6741

区分 呼び mm	V P							V U					
	外 径			厚 さ		近 似 内 径 (mm)	1m当り の重さ (参考)	外 径		厚 さ		近 似 内 径 (mm)	1m当り の重さ (参考)
	基 本 寸 法 (mm)	最大・最 小外径の 許容差 (mm)	平 均 外径の 許容差 (mm)	最 小 寸 法 (mm)	許容差 (mm)			基 本 寸 法 (mm)	平 均 外径の 許容差 (mm)	最 小 寸 法 (mm)	許容差 (mm)		
13	18	±0.2	±0.2	2.2	±0.6	13	174	-	-	-	-	-	-
16	22	±0.2	±0.2	2.7	±0.6	16	256	-	-	-	-	-	-
20	26	±0.2	±0.2	2.7	±0.6	20	310	-	-	-	-	-	-
25	32	±0.2	±0.2	3.1	±0.8	25	448	-	-	-	-	-	-
30	38	±0.3	±0.2	3.1	±0.8	31	542	-	-	-	-	-	-
40	48	±0.3	±0.2	3.6	±0.8	40	791	48	±0.2	1.8	±0.4	44	413
50	60	±0.4	±0.2	4.1	±0.8	51	1122	60	±0.2	1.8	±0.4	56	521
65	76	±0.5	±0.3	4.1	±0.8	67	1445	76	±0.3	2.2	±0.6	71	825
75	89	±0.5	±0.3	5.5	±0.8	77	2202	89	±0.3	2.7	±0.6	83	1159
100	114	±0.6	±0.4	6.6	±1.0	100	3409	114	±0.4	3.1	±0.8	107	1737
125	140	±0.8	±0.5	7.0	±1.0	125	4464	140	±0.5	4.1	±0.8	131	2739
150	165	±1.0	±0.6	8.9	±1.4	146	6701	165	±0.6	5.1	±0.8	154	3941
200	216	±1.3	±0.8	10.3	±1.4	194	10129	216	±0.8	6.5	±1.0	202	6572
250	267	±1.6	±1.0	12.7	±1.8	240	15481	267	±1.0	7.8	±1.2	250	9758
300	318	±1.9	±1.1	15.1	±2.2	286	21962	318	±1.1	9.2	±1.4	298	13701
350	-	-	-	-	-	-	-	370	±1.3	10.5	±1.4	348	18051
400	-	-	-	-	-	-	-	420	±1.5	11.8	±1.6	395	23059
450	-	-	-	-	-	-	-	470	±1.7	13.2	±1.8	442	28875
500	-	-	-	-	-	-	-	520	±1.9	14.6	±2.0	489	35346
600	-	-	-	-	-	-	-	630	±3.2	17.8	±2.8	592	52679
700	-	-	-	-	-	-	-	732	±3.7	21.0	±3.2	687	72018
800	-	-	-	-	-	-	-	835	±4.2	23.9	±3.8	783	93781